

Tanktop Mounted Return Line Filter - TTF Series

Part #: TTF305QVP2EG161



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#)  [Share / Email](#)  [Print](#) 

Technical Specifications

Flow Capacity (l/min):	90 *	Indicator Type:	No indicator, port plugged L+R
Bypass Valve (bar):	1,5 *	Product Series:	TTF Series
Port Connection Type:	G1 *	Options:	No Diffuser
Filter Element:	05Q Microglass	Product Style:	Tanktop Mounted Return Line Filter
Flow Rate:	0 to 85 l/min	Seal Material:	Fluoroelastomer
Brand:	Parker	Bypass Valve Pressure Rating:	1.5 bar
Bypass Valve Pressure Rating:	1.5 bar	Operating Pressure:	10 bar, 150 psi
Division:	Hydraulic & Industrial Process Filtration Division	Operating Temperature:	-20 to 120 °C
Connection Type:	G1	Filter Element Type:	05Q Microglass
Industry:	Trucks and Buses, Materials Handling, Construction	Mounting Type:	Tanktop Mounted
Filter Element Type:	05Q Microglass	Housing Material:	Aluminium
Application:	Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
Micron Rating:	5 µm	Indicator Pressure Setting:	No indicator
Technology:	Filtration, Hydraulics		
Product Type:	Hydraulic Oil Filters		

 [Safety Warning](#)

Item Information

Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

Features and Benefits



can be utilised for severe return line applications for reduced downtime due to premature filter failures

[Home](#)

- Patented *LEIF*® elements safeguard filtration quality

[Products](#) ▾

- Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time

[Help & Support](#)

- In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter

[Industries](#)

- Quick response bypass with low hysteresis for improved system protection.

[CAD Drawings + Files](#)

[Where To Buy](#)



[Related Documents](#)



Americas

USA, Canada, Mexico

cparker@support.parker.com

[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

[+ Company Information](#)

[+ Global Operations](#)

[+ Help & Support](#)

[+ Follow Us :](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)
