

Tanktop Mounted Return Line Filter - TTF Series

Part # **TTF502QLBS1EG163**



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|--|-------------------------------|------------------------------------|
| Flow Capacity (l/min): | 150 * | Technology: | Filtration, Hydraulics |
| Bypass Valve (bar): | 1,5 * | Indicator Type: | Electrical 42V, NO/NC, M10x1 |
| Filter Element: | 02QL Ecoglass | Product Type: | Hydraulic Oil Filters |
| Port Connection Type: | G1 * | Options: | Diffuser type T |
| Flow Rate: | 0 to 75 l/min | Product Series: | TTF Series |
| Brand: | Parker | Product Style: | Tanktop Mounted Return Line Filter |
| Bypass Valve Pressure Rating: | 1.5 bar | Seal Material: | Nitrile |
| Division: | Hydraulic & Industrial Process Filtration Division EMEA | Bypass Valve Pressure Rating: | 1.5 bar |
| Connection Type: | G1 | Operating Pressure: | 10 bar, 150 psi |
| Industry: | Trucks and Buses, Materials Handling, Construction | Operating Temperature: | -40 to 100 °C |
| Filter Element Type: | 02QL Ecoglass | Filter Element Type: | 02QL Ecoglass |
| Application: | Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment | Mounting Type: | Tanktop Mounted |
| Micron Rating: | 2 µm | Indicator Pressure Setting: | 1.2 bar |

[Safety Warning](#)

Item Information

Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

Features and Benefits

- 10 bar rated filter can be utilised for severe return line applications for reduced downtime due to premature filter failures



elements safeguard filtration quality

[Home](#)

• Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time

[Products](#)

• In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter

[Support](#)

• Quick response bypass with low hysteresis for improved system protection.

[Industries](#)

CAD Drawings + Files



[Services](#)

Related Documents

[Solutions](#)



[Where to Buy](#)



Parker Sales Company UK

psc.uk.webform@support.parker.com

[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
