



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

[Home](#) / [Products](#) / [Filters, Collectors, Separators](#) / [Filter Assemblies and Vessels](#) / [Hydraulic Filters](#) / [Tanktop Mounted Return Line Filters](#) / TTF710QBP2EG324

# Tanktop Mounted Return Line Filter - TTF Series

Part #: TTF710QBP2EG324



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Brand:	Parker	Indicator Type:	No indicator, port plugged L+R
Flow Rate:	0 to 400 l/min	Product Series:	TTF Series
Bypass Valve Pressure Rating:	1.5 bar	Options:	Diffuser type P
Division:	Hydraulic & Industrial Process Filtration Division	Product Style:	Tanktop Mounted Return Line Filter
Connection Type:	EME A	Seal Material:	Nitrile
Industry:	G2	Bypass Valve Pressure Rating:	1.5 bar
Filter Element Type:	Trucks and Buses, Materials Handling, Construction	Operating Pressure:	10 bar, 150 psi
Application:	10Q Microglass	Operating Temperature:	-40 to 100 °C
Micron Rating:	Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment	Filter Element Type:	10Q Microglass
Technology:	10 µm	Mounting Type:	Tanktop Mounted
Product Type:	Filtration, Hydraulics	Indicator Pressure Setting:	No indicator
	Hydraulic Oil Filters		

[Safety Warning](#)

## Item Information



Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

Features and Benefits

- 10 bar rated filter can be utilised for severe return line applications for reduced downtime due to premature filter failures
- Patented *LEIF*® elements safeguard filtration quality
- Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time
- In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter
- Quick response bypass with low hysteresis for improved system protection.

CAD Drawings + Files +

Related Documents +



Parker Sales Company UK

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)

+44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :



