

Tanktop Mounted Return Line Filter - TTF Series

[Solutions](#)

Part #: TTF710QLBP2E2G243

[Where to Buy](#)

The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 400 l/min	Indicator Type:	No indicator, port plugged L+R
Brand:	Parker	Options:	Diffuser type T
Bypass Valve Pressure Rating:	1.5 bar	Product Series:	TTF Series
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Seal Material:	Nitrile
Connection Type:	2 x G1½	Product Style:	Tanktop Mounted Return Line Filter
Industry:	Trucks and Buses, Materials Handling, Construction	Bypass Valve Pressure Rating:	1.5 bar
Filter Element Type:	10QL Ecoglass	Operating Pressure:	10 bar, 150 psi
Application:	Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment	Operating Temperature:	-40 to 100 °C
Micron Rating:	10 µm	Filter Element Type:	10QL Ecoglass
Technology:	Filtration, Hydraulics	Mounting Type:	Tanktop Mounted
Product Type:	Hydraulic Oil Filters	Indicator Pressure Setting:	No indicator

[Safety Warning](#)

Item Information

Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the “In-to-Out” filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

Features and Benefits

- 10 bar rated filter can be utilised for severe return line applications for reduced downtime due to premature filter failures



- Parker H/E/EC elements safeguard filtration quality
- Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time
- In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter
- Quick response bypass with low hysteresis for improved system protection.

[Support](#)

CAD Drawings + Files



[Industries](#)

Related Documents



[Solutions](#)

[Where to Buy](#)



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

