

# Tanktop Mounted Return Line Filter - TTF Series

Part #: TTF710QLBP2EG324



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#)
[Share / Email](#)
[Print](#)

## Technical Specifications

<b>Brand:</b>	Parker	<b>Product Type:</b>	Hydraulic Oil Filters
<b>Flow Rate:</b>	0 to 400 l/min	<b>Product Series:</b>	TTF Series
<b>Bypass Valve Pressure Rating:</b>	1.5 bar	<b>Options:</b>	Diffuser type P
<b>Division:</b>	Hydraulic & Industrial Process Filtration Division EMEA	<b>Product Style:</b>	Tanktop Mounted Return Line Filter
<b>Connection Type:</b>	G2	<b>Seal Material:</b>	Nitrile
<b>Industry:</b>	Trucks and Buses, Materials Handling, Construction	<b>Bypass Valve Pressure Rating:</b>	1.5 bar
<b>Filter Element Type:</b>	10QL Ecoglass	<b>Operating Pressure:</b>	10 bar, 150 psi
<b>Application:</b>	Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment	<b>Operating Temperature:</b>	-40 to 100 °C
<b>Micron Rating:</b>	10 µm	<b>Filter Element Type:</b>	10QL Ecoglass
<b>Technology:</b>	Filtration, Hydraulics	<b>Mounting Type:</b>	Tanktop Mounted
<b>Indicator Type:</b>	No indicator, port plugged L+R	<b>Indicator Pressure Setting:</b>	No indicator

[Safety Warning](#)

## Item Information



Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

#### Features and Benefits

- 10 bar rated filter can be utilised for severe return line applications for reduced downtime due to premature filter failures
- Patented *LEIF*® elements safeguard filtration quality
- Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time
- In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter
- Quick response bypass with low hysteresis for improved system protection.

## CAD Drawings + Files



## Related Documents



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



