

# Tanktop Mounted Return Line Filter - TTF Series

Part #: TTF720QBG1EG203



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

|                               |  |                               |                                    |
|-------------------------------|--|-------------------------------|------------------------------------|
| Bypass Valve (bar):           | 1,5 *  | Technology:                   | Filtration, Hydraulics             |
| Flow Capacity (l/min):        | 230  | Indicator Type:               | Visual M10x1                       |
| Port Connection Type:         | G1¼ *  | Product Type:                 | Hydraulic Oil Filters              |
| Filter Element:               | 20Q Microglass *   | Options:                      | Diffuser type T                    |
| Flow Rate:                    | 0 to 450 l/min   | Product Series:               | TTF Series                         |
| Brand:                        | Parker   | Seal Material:                | Nitrile                            |
| Division:                     | Hydraulic & Industrial Process Filtration Division<br>EMEA                   | Product Style:                | Tanktop Mounted Return Line Filter |
| Bypass Valve Pressure Rating: | 1.5 bar  | Bypass Valve Pressure Rating: | 1.5 bar                            |
| Connection Type:              | G1¼  | Operating Pressure:           | 10 bar, 150 psi                    |
| Industry:                     | Trucks and Buses, Materials Handling, Construction                           | Operating Temperature:        | -40 to 100 °C                      |
| Filter Element Type:          | 20Q Microglass   | Filter Element Type:          | 20Q Microglass                     |
| Application:                  | Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment | Mounting Type:                | Tanktop Mounted                    |
| Micron Rating:                | 20 µm  | Indicator Pressure Setting:   | 1.2 bar                            |

[Safety Warning](#)

## Item Information

Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

### Features and Benefits



• 10 micron filter can be utilised for severe return line applications for reduced downtime due to premature filter failures

• Pleated filter elements safeguard filtration quality

**Home**  
• Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time

**Products**  
• In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter

**Support**  
• Quick response bypass with low hysteresis for improved system protection.

**Industries**

## CAD Drawings + Files



**Services**

## Related Documents



**Where to Buy**



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---

