

<u>Home</u>

Products

Support

Hndustries / Filters, Collectors, Separa... / Filter Assemblies and Vessels / Hydraulic Filters / Tanktop Mounted Return Line... / TTF720QLBS1EG203

Taiktop Mounted Return Line Filter - TTF Series

Solutions Part #: TTF720QLBS1EG203 Where to Buy



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

View Series Page 🚍 Share / Email 🔿 Print 🖶

Technical Specifications

Bypass Valve (bar):	1,5 *	Technology:	Filtration, Hydraulics
Flow Capacity (I/min):	230	Indicator Type:	Electrical 42V, NO/NC, M10x1
Port Connection Type:	G1¼ *	Product Type:	Hydraulic Oil Filters
Filter Element:	20QL Ecoglass *	Options:	Diffuser type T
Flow Rate:	0 to 450 l/min	Product Series:	TTF Series
Brand:	Parker	Seal Material:	Nitrile
Bypass Valve Pressure	1 E har	Product Style:	Tanktop Mounted Return Line Filter
Rating:	1.5 bar	Bypass Valve Pressure	1 5 4
Division:	Hydraulic & Industrial Process Filtration Division	Rating:	1.5 bar
	EMEA	Operating Pressure:	10 bar, 150 psi
Connection Type:	G1¼	Operating Temperature:	-40 to 100 °C
Industry:	Trucks and Buses, Materials Handling, Construction	Filter Element Type:	20QL Ecoglass
Filter Element Type:	20QL Ecoglass	Mounting Type:	Tanktop Mounted
Application:	Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment	Indicator Pressure	1.2 bar
Micron Rating:	20 μm	Setting:	

▲ Safety Warning

Item Information

Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 har. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

Features and Benefits



can be utilised for severe return line applications for reduced downtime due to premature filter failures

Carker Contraction quality

Home • Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time

Products. • In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter

Support QUICK response bypass with low hysteresis for improved system protection.

CAD Drawings + Files ╋ Services Related Documents

Where to Buy



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

 \bigcirc

7



<u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy