

[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

Home / Products / Filters, Collectors, Separators / Filter Assemblies and Vessels / Hydraulic Filters / Tanktop Mounted Return Line... / TTF920QBP2BG203

Tanktop Mounted Return Line Filter - TTF Series

Part #: TTF920QBP2BG203



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|--|-------------------------------|------------------------------------|
| Flow Rate: | 0 to 550 l/min | Indicator Type: | No indicator, port plugged L+R |
| Brand: | Parker | Options: | Diffuser type T |
| Bypass Valve Pressure Rating: | 0.8 bar | Product Series: | TTF Series |
| Division: | Hydraulic & Industrial Process Filtration Division EMEA | Product Style: | Tanktop Mounted Return Line Filter |
| Connection Type: | G1 1/4 | Seal Material: | Nitrile |
| Industry: | Trucks and Buses, Materials Handling, Construction | Bypass Valve Pressure Rating: | 0.8 bar |
| Filter Element Type: | 20Q Microglass | Operating Pressure: | 10 bar, 150 psi |
| Application: | Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment | Operating Temperature: | -40 to 100 °C |
| Micron Rating: | 20 µm | Filter Element Type: | 20Q Microglass |
| Technology: | Filtration, Hydraulics | Mounting Type: | Tanktop Mounted |
| Product Type: | Hydraulic Oil Filters | Indicator Pressure Setting: | No indicator |

[Safety Warning](#)

Item Information



Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

Features and Benefits

- 10 bar rated filter can be utilised for severe return line applications for reduced downtime due to premature filter failures
- Patented *LEIF*® elements safeguard filtration quality
- Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time
- In-to-out filtration means captured contamination is retained inside the element preventing recontamination of the filter
- Quick response bypass with low hysteresis for improved system protection.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44201926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



