

[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

Filter Pressure and Vacuum Indicator - FMU and LPS Series | #UT11019

[☰ View Series Page](#)



Local Contact

Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

Phone


+44 (0)1926 317878

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.

Register now

A comprehensive range of high quality indicators for mobile, industrial and marine applications.

 Share / Email

Technical Specifications

Maximum Fluid Temperature:

80°C

Indicator Type:

Electrical Switch N.C.

Indicator Pressure Setting:

1.0 bar

Seal Material:

n/a

Housing Material:

Brass

Port Connection:

G $\frac{1}{8}$ " Conical

Port Location:

Below

Maximum Operating Pressure:

80 bar

Electrical Connection:

Protective Connector PG7

Power Supply Voltage:

48V

 **Safety Warning**

Item Information

Measuring critical system parameters is essential, FMU and LPS indicators enable reliable and continuous control of the filter in all applications.

Ideal for giving accurate electrical feedback of filter clogging condition in order to facilitate effective maintenance and ensuring hydraulic systems, marine/mobile or industrial are protected from particulate contamination.

Designed for use on a wide range of Parker filters and suitable for competitive interchange (consult Parker Filtration for details).

Product Features:

- Accurate visual, electronic or electrical filter condition feedback

Typical Applications

- Industrial equipment
- Mobile equipment
- Marine/offshore applications

— Show Less

CAD Drawings + Files

No CAD files available



Parker Sales Company UK

+44 (0)1926 317878

psc.uk.webform@support.parker.com

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)