

Marine Fuel Filter Water Separator – Racor Turbine Series | #1000MAM30

 [View Series Page](#)



Local Contact

Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

Phone

+44 (0)1926 317878

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.



Register now



Marine 1000 Turbine Series with Aluminum Alloy Bowl, 7/8-14 UNF-2B Female ports, 98%@30 Micron media

[Share / Email](#)

Technical Specifications

Valve Type:

n/a

Flow Rate:

180 gph (681 lph)

Connection Type:

7/8"-14 UNF-2B Female

Micron Rating:

98% @ 30 Micron

Materials of Construction:

Bowl: Aluminium Alloy

Water Sensor Option:

n/a

Product Series:

Cartridge FF/WS, Marine 1000 Turbine

Brand:

Racor

For Fluid Type:

Diesel Fuel / B20

Mounting Type:

Bracket Included

Number of Housings:

1

Clean Pressure Drop:

0.03 bar, 0.49 psi

Pump Type:

Electric Primer Pump Option: RKP1912/RKP1924

Number of Ports:

2

Filter Element Type:

Top loaded element cartridge with 30 Micron Aquabloc® Media

Compatible Element:

2020N-30

Application:

Marine fuel filtration

Materials of Construction:

Powder Coated Aluminum Alloy

Maximum Continuous Pressure:

15 psi / 1.03 bar

Item Information

The Racor Marine Fuel Filter Water Separator Turbine Series is the most trusted fuel filter water separator on the market. The UL-approved assembly features a three-stage filtration system that effectively removes water and particulates from fuel, providing maximum protection of diesel engine components in marine applications where reliability is critical.

Racor marine fuel filter water separators are available in a wide range of configurations to meet the unique requirements of customer's engines. All models utilize Racor's proprietary Aquabloc® filtration elements. Aquabloc® is a unique engineered media that incorporates pleat-spacing corrugations and a graduated pore structure to increase dirt-holding capacity and extend filter life. The media is waterproof and rustproof, capturing contaminants while the specially treated surface separates and coalesces water from the fuel, which causes the water to gather into large droplets that then fall into the clear collection bowl. Aquabloc® elements are available in three different ratings, including:

30 micron (98%@30 micron) – Ideally suited as a pre-filter to protect downstream filters from excessive contamination. Extends the life of on-engine filters.

10 micron (98%@10 micron) - Captures more contaminants than 30 micron elements, and is more effective at stopping water. Extends the life of the entire fuel system.

"2" micron (98%@4 microns) – Provides maximum water removal and filtration and is capable of protecting all modern injection systems, while greatly extending the life of difficult-to-service on-engine filters.

How They Work

For optimal performance, Turbine Series marine filter assemblies should be installed on the vacuum side of the fuel transfer pump. They remove contaminants from fuel using the following three-stage process:

Stage One - Water Separation: As fuel enters the filter assembly, it moves through the centrifuge and spins off large solids and water droplets, which fall to the bottom of the collection bowl.

Stage Two - Coalescing: Small water droplets bead-up on the surface of the conical baffle and cartridge element. When heavy enough, they fall to the bottom of the bowl.

Stage Three - Filtration: Proprietary Aquabloc® cartridge stops and captures fine hard and soft contaminants, while remaining water coalesces on the media surface. The coalesced water gathers into larger drops that then fall down into the clear collection bowl.

Markets:

- Construction
- Power Generation
- Oil and Gas

Applications:

- Diesel and Biodiesel Engines used in marine/water environments

Benefits:

- Removes water that enters the system through condensation in the fuel tank. Any water present in the fuel

- Removes hard particles present in air that are introduced during fueling, such as sand and silica.
- Removes soft contaminant particles from overheated and degraded diesel fuel, which coat filters with black asphaltene-like substance, leading to power loss and engine shutdown.
- Prevents costly injector damage and increases operational life of downstream filters.
- Saves time and money by eliminating unplanned maintenance and unscheduled downtime from system component failure.
- With Racor 75 and 791000 Turbines, a simple turn of a valve puts a clean filter back on-line. Servicing of the clogged filter can then be performed with the engine running.
- Available in a wide range of configurations to meet the unique requirements of customers' engines, including marine (UL-approved) versions.

Features:

- Aquabloc® engineered media elements with 98% efficiency at 4, 10 or 30 micron
- Various flow rates available: 60 gph (227 lpm) with a single 500FG Series, up to 540 gph (2044) with the 77 and 791000 series triple-manifold units
- Corrosion-resistant construction
- Self-venting drain valve or plug (on metal bowls)
- Clear contaminant collection bowl

— Show Less

CAD Drawings + Files

No CAD files available



Parker Sales Company UK

+44 (0)1926 317878

parker.uk@parker.com

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :



© PARKER HANNIFIN CORP 2023



ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



















































