



[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Fuel Filters](#) / [Disposable Fuel F...](#) / 23281-30

# Disposable Fuel Filter / Water Separator – SNAPP™ Series

**Solutions**  
**Part #:** 23281-30  
**Where to Buy**



Racor SNAPP First Fit, White Body and Stainless Steel Bracket, No Drain, (2) 3/8" Straight Quick Connect Fittings, 30 Micron Rated

[View Series Page](#) [Share / Email](#) [Print](#)

Qty:

1

[Request Quote](#)



This product is fulfilled by an authorized Parker distributor or division.

**Find a Distributor**

[Where to Buy](#)

[Save to Product List](#)

**Division Contact**

Parker Sales Company UK

Pilot Way | Ansty Business Park  
 Coventry CV7 9JU  
 Ph: +44 (0)1926 317878

## Technical Specifications

<b>Product Series:</b>	Disposable FF/WS, SNAPP™	<b>Depth:</b>	4.09 in/10.30 cm, 4.1 inch, 104 cm
<b>Configuration:</b>	White Body and Stainless Steel Bracket	<b>Weight:</b>	1.0 lb/.45 kg, 1 lb, 0.45 kg
<b>Use Case:</b>	First Fit	<b>Element Removal Clearance:</b>	2.5 in/6.35 cm) inch
<b>Bowl Type:</b>	No Drain	<b>Connection Size:</b>	3/8" Quick connect
<b>Brand:</b>	Racor	<b>Includes:</b>	(2) 3/8" Straight Quick Connect Fittings
<b>For Fluid Type:</b>	Gasoline/Diesel	<b>Optional Accessories:</b>	Fittings 2-Pack: RK23319: 3/8" Quick Connect Elbow Fitting RK23320: 5/16" Quick Connect Straight Fitting RK23321: 5/16" Quick Connect Elbow Fitting
<b>Configuration:</b>	First Fit	<b>Inlet Port Size:</b>	3/8" Quick connect
<b>Mounting Type:</b>	Stainless Steel Bracket	<b>Materials of Construction:</b>	Glass filled Nylon body, Nylon bowl, stainless steel bracket
<b>Bowl Type:</b>	No Drain	<b>Maximum Operating Temperature:</b>	-20 to 150 °F, -29 to 66 °C
<b>Media:</b>	30 Micron Rated (26 gph gasoline/26 gph diesel)	<b>Compatible Element:</b>	R23280-30
<b>Media:</b>	30 Micron Rated		
<b>Flow Rate:</b>	26 (gasoline)/26 (diesel) Gal/hour, 98 (gasoline)/98 (diesel) L/hour		
<b>Height:</b>	7.82 in/19.86 cm, 7.8 inch, 19.8 cm		
<b>Width:</b>	3.83 in/9.73 cm, 3.8 inch, 9.7 cm		

[Safety Warning](#)

## Item Information

The SNAPP™ Series is a compact, disposable fuel filter water separator with premium filtration capabilities. Unlike conventional small engine filters, which use a spin-on element that requires a strap wrench to service, the SNAPP™ filter features a patented bracket system and quick-connect fittings that eliminate the need for seals or threads. This allows change-outs to be performed quickly, easily, and without the use of tools. The filter only requires 2-1/2 inches front clearance for servicing, making it suitable for installation wherever you need it.

The SNAPP™ filter housing's one-piece, high-impact nylon structure is coupled with a powder-coated or stainless steel (for marine use) mounting bracket to resist corrosion in all environments. The clear collection bowl allows for accurate inspection of fuel quality. A self-vent drain is also available for easy removal of collected water.

At the heart of the SNAPP™ fuel filter is Racor's proprietary Aquabloc® technology. Aquabloc® is a unique engineered media that incorporates pleat-spacing corrugations and a graduated pore structure to increase dirt-holding capacity and extend filter life. The media is waterproof and rustproof, capturing contaminants while the specially treated surface separates and coalesces water from the fuel, causing the water to gather into large droplets that then fall into the clear collection bowl.

Aquabloc® elements are available in three different ratings, including:

30 micron (98%@30 micron) – Ideally suited as a pre-filter to protect downstream filters from excessive contamination. Extends the life of on-engine filters. Flow up 26 gph (129 lph) in both gasoline and diesel using the SNAPP™ filter.

10 micron (98%@10 micron) - Captures more contaminants than 30 micron elements, and is more effective at stopping water. Extends the life of the entire fuel system. Flow up 34 gph (129 lph) in gasoline and 26 gph (98 lpm) diesel using the SNAPP™ filter.

"2" micron (98%@4 microns) – Provides maximum water removal and filtration and is capable of protecting all modern injection systems, while greatly extending the life of difficult-to-service on-engine filters. Flow up 40 gph (151 lph) in gasoline and 26 gph (98 lpm) in diesel using the SNAPP™ filter.

### How it Works

The SNAPP™ filter can be installed in the fuel line between the tank and the engine. The filter "snaps" into its mounting bracket. The quick-connect fittings allow for fast connection to fuel lines. The inlet and outlet ports can be positioned as necessary by flipping the SNAPP™ filter in the bracket. Changing the filter can be done by squeezing the quick release fitting tabs, removing and priming the new filter (flow outlet of old to inlet of new), re-attaching fuel lines, and snapping the new filter into the bracket.

### Markets:

- Agriculture
- Construction
- Power Generation
- Oil and Gas
- Marine

### Applications:

- Diesel and Biodiesel Engines
- Gasoline Engines

### Benefits:

- At just 4 inches wide with 2 to 2-1/2 inch bolt spacing, the SNAPP™ filter and bracket easily replaces existing filters and can be mounted anywhere you need it.



[Home](#) [Products](#) [Features and Specifications](#) [Support](#) [Industries](#) [Services](#) [Solutions](#) [Where to Buy](#)

fittings eliminate the need for tools, making filter change-outs quick, easy, and painless. that enters the system through condensation in the fuel tank. Any water present in the fuel stream will support bacterial growth, clogged filters and result in the formation of corrosive acids. Susceptible components then rust and corrode, leading to erosion and wear of critical fuel system components.

Removes hard particles present in air that are introduced during fueling, such as sand and silica.

Saves time and money by eliminating unplanned maintenance and unscheduled downtime from system component failure.

Suitable for use in both marine and non-marine applications

**Features and Specifications:**

**Support:**

- Designed for engines with a fuel flow rates up to 40 gph (151 lph) in gasoline and 26 gph (98 lph) in diesel
- Heavy-duty, corrosion-proof, high-impact nylon construction

**Industries:**

- Non-resistant, permanent stainless steel or powder-coated steel mounting bracket
- Universal bracket accommodates 2 to 2-1/2 inch bolt spacing

**Services:**

- Available straight quick connects for 3/8" hose included.
- Patented Aquabloc® media comes in "2", 10 or 30 micron rating

**Solutions:**

- Collection bowl with self-venting drain (optional closed bowl)
- Compatible with E10 gasoline, diesel, biodiesel up to B20

**Where to Buy:**

- Compatible with 50 psi pressure spikes

### CAD Drawings + Files

### Related Documents

### Related Products

<
>

**Replacement Filter Elements – Racor Spin-on Series**

**Fuel Filter Water Separator – Racor Spin-on Series**

**Marine Fuel Filter Water Separator – Racor Spin-on Series**

**Marine Replacement Filter Elements – Racor Marine Spin-on Series**

**Fuel Spin-on Bowl and Water Sensor Kits - Racor**

**Gauges and Replacement Parts - Racor**

**Fuel Prefilters and Strainers – Racor 025 and PS120 Series**



**Parker Sales Company UK**

Pilot Way | Ansty Business Park

- [Company Information](#)
- [Global Operations](#)
- [Help & Support](#)
- [Follow Us :](#)

© PARKER HANNIFIN CORP 2024  
**ENGINEERING YOUR SUCCESS.**  
[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

