

Cartridge Engine Air Filters – Racor ECO, AF, and EA Series | #AFCS071

 [View Series Page](#)



Local Contact

Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

Phone

+44 (0)1926 317878

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.



Racor Cartridge Engine Air Filters ensure delivery of clean, purified air into gasoline and diesel engines. They come available with a wide range of flow rate and mounting options, making them suitable for use in any engine or application.

[Share / Email](#)

Technical Specifications

Pre-Cleaner:

Dynamic Vane

Filter Element Type:

Primary Air and Safety Filters

Flow Range:

124 to 159 cfm (3.5 to 4.5 m³/m)

Maximum Flow Rate:

200 cfm (6 m³/m)

Connection Type:

Straight

Materials of Construction:

Coated Steel

Application:

Heavy Dust

Brand:

Racor

Product Series:

AFCS, Cartridge Air

For Fluid Type:

Engine Air

Outlet Connection Size:

2.5 in/6.4 cm

Output Power:

50 to 70 HP (37 to 52 KW) HP

Inlet Connection Size:

No Connection

Length:

19.3 in/49 cm

Outside Diameter:

7.4 in/18.8 cm

Mounting Position:

Horizontal or Vertical

Compatible Mounting Clamp:

Included

Compatible Element:

Primary: AR6060

Accessories Included:

See literature on Product Support tab

Item Information

Racor AFCS Combination Pre-Cleaner/Air Filter Series – About:

Heavy duty equipment requires heavy duty engine air intake filtration. Racor’s AFCS air filters with integral pre-cleaners are designed and built to meet the requirements for hard working gasoline and diesel powered engines. They are suitable for high dust environments with excessive vibration and extreme temperatures. Racor AFCS air filters are the economical choice for your heavy duty applications. Replacing the existing air filter with a Racor combination system requires just a few additional inches in length and is normally maintenance free. The pre-cleaner is self-powered and self-cleaning, requiring no electrical or exhaust gas power to dispose of the separated particles.

Racor AFCS Combination Pre-Cleaner/Air Filter Series - How They Work:

Air enters the pre-cleaner portion through static vanes causing the air to spin. As the air spins, centrifugal force separates dust, dirt, insects, rain, and snow from the air stream. The swirling air drives a high velocity rotor that acts as a blower, evacuating contaminants through special discharge ports in the side of the assembly. Only purified air flows to the air filter stage. Applications include agricultural machinery, earth moving equipment, construction, mining equipment, stationary engines, generator sets, big rig trucks, pick-ups, off road vehicles, material handling equipment, snow removal equipment, street sweepers, and any engine from 30 to 260 HP (22 to 194 KW).

Racor AFCS Combination Pre-Cleaner/Air Filter Series - Additional Features and Benefits:

- Flow Range: 53 to 1517 cfm (1.5 to 43 m³/min) (Depending on product selected)
- Engine Power Range: 30 to 260 HP (22 to 194 KW) (Depending on product selected)
- Pre-cleaner static vanes remove up to 90% of large contaminants
- Horizontal mounting with adjustable mounting band
- Safety element is standard on most models
- Powder coated steel housing and bracket

— Show Less

CAD Drawings + Files

No CAD files available



Parker Sales Company UK

+44 (0)1926 317878

parker.uk@parker.com

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)