

Cartridge Engine Air Filters – Racor ECO, AF, and EA Series | #AFSF12

 [View Series Page](#)



Local Contact

Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

Phone

+44 (0)1926 317878

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.



Register now



Racor Cartridge Engine Air Filters ensure delivery of clean, purified air into gasoline and diesel engines. They come available with a wide range of flow rate and mounting options, making them suitable for use in any engine or application.

[Share / Email](#)

Technical Specifications

Pre-Cleaner:

Static Vane

Filter Element Type:

Primary Air and Safety Filters

Flow Range:

282 to 423 cfm (8.0 to 12.0 m³/m)

Maximum Flow Rate:

600 cfm (17 m³/m)

Connection Type:

Straight

Materials of Construction:

Coated Steel

Application:

Heavy Dust

Brand:

Racor

Product Series:

AFSF, Cartridge Air

For Fluid Type:

Engine Air

Outlet Connection Size:

4 in/10.2 cm

Output Power:

120 to 160 HP (90 to 119 KW) HP

Inlet Connection Size:

4 in/10.2 cm

Length:

18.8 in/47.8 cm

Outside Diameter:

10 in/25.4 cm

Mounting Position:

Horizontal

Compatible Mounting Clamp:

Included

Compatible Element:

Primary: AR6067

Accessories Included:

See literature on Product Support tab

Item Information

Racor AFSF Air Filter Series – About:

Racor AFSF Series standard air filters are heavy-duty three-stage air filters for on-highway and stationary applications and are designed to be connected to the air intake of gasoline or diesel engines. They have a static vane first stage, followed by standard primary and safety elements. The housing and universal mounting bracket are powder coated steel for a durable, corrosion resistant finish. The standard tube-style inlet is suitable for use with Racor dynamic rotor pre-cleaners.

Racor AFSF Air Filter Series - How They Work:

Air flows through stationary vanes causing the entering air to spin. The resulting centrifugal force separates the heaviest impurities (dust, dirt, insects and other debris) from the air stream. These contaminants are discharged automatically through an integral evacuator valve. Only purified air flows to the air filters (primary and safety stages of filtration).

Racor AFSF Air Filter Series - Additional Features and Benefits:

- Flow Range: 53 to 1517 cfm (1.5 to 43 m³/min) (Depending on product selected)
- Engine Power Range: 30 to 450 HP (22 to 336 KW) (Depending on product selected)
- Pre-cleaner static vanes remove up to 90% of large contaminants
- Horizontal mounting
- Safety element is standard
- Powder coated steel housing and bracket
- Includes mounting bands

— Show Less

CAD Drawings + Files

No CAD files available



+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)