


[Home](#)
[Products](#)
[Support](#)
[Industries](#)
[Services](#)
[Solutions](#)
[Where to Buy](#)
[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Compressed Air an...](#) / [Natural Gas Filters](#) / [Compressed Natura...](#) / [CLS116-10](#)

Compressed Natural Gas (CNG) Service Elements – Racor FFC Series

Part #: CLS116-10



Coalescer grade 10 Element for FFC-116N Housing

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Height (cm):	5.8	Diameter:	0.8 inch, 2 cm
Product Series:	Cartridge CNG Fuel Filter, FFC Series	Media:	Coalescer grade 10
Brand:	Racor	Filter Housing Series:	FFC-116N
For Fluid Type:	CNG	Height (inch):	2.3
Application:	Onboard CNG powered vehicles		

[Safety Warning](#)

Item Information

FFC Series Replacement (Type C) Coalescer Elements for Compressed Natural Gas (CNG) Filtration

Note: Images are for reference only and may not represent actual product selected.

FFC series filters are designed to protect critical engine components in CNG powered vehicles. Racor CLS replacement elements are specifically designed to remove oil, water, and solid contamination from compressed natural gas. The patented coalescing filter removes 99.97% of all aerosols in the 0.3 to 0.6 micron range.

These CNG coalescer elements are produced by a patented process of arranging micro-glass fibers into a tubular form. During operation, Dirty, wet CNG is forced through the coalescing media from the inside of a cartridge through a tubular wall to the outside, where large droplets fall to the bottom of the housing. Clean CNG gas exits the housing through the outlet port. Oil and water removed from the gas stream accumulates until drained, while dirt particles are trapped and retained on surfaces of the fibers.

Type C Media Grades to Order:

Grade 6

Grade 6 filter elements are used when "total removal of liquid aerosols and suspended fines" is required. Because of its overall performance characteristics, this grade is most often recommended below 500 PSIG.

Grade 10

Grade 10 filters are used as pre-filters for grade 6 to remove gross amounts of aerosols or tenacious aerosols which are difficult to drain. This grade is often used as a 'coarse' coalescer.

CAD Drawings + Files

Related Documents

Qty:

[Request Quote](#)


This product is fulfilled by an authorized Parker distributor or division.

[Find a Distributor](#)
[Where to Buy](#)
[Save to Product List](#)

Division Contact

Parker Sales Company UK

 Pilot Way | Ansty Business Park
 Coventry CV7 9JU
 Ph: +44 (0)1926 317878


Parker Sales Company UK

Pilot Way | Ansty Business Park

psc.uk.webform@support.parker.com

Company Information



[Global Operations](#)

[Help & Support](#)

[Follow Us :](#)

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

